

get_messagestate.asp

DEPRECATED

Return message states

Description

get_messagestate.asp?company=RTI_COMPANYKEY&vehicle=RTI_VEHICLEKEY&language=deu&DATEFROM=YYYYMMDD&DATETO=YYYYMMDD&timefrom=HHMMSS&timeto=HHMMSS&datatype=insertdate

Parameter

Parameter	Description	Type	Note	Mandatory
company	RTI company key	string		yes
vehicle	RTI vehicle key	string	only used for secondary authentication	yes
language	define output language	string	- kein Wert oder "deu" = Deutsch "gbr" = englisch "fra" = französisch "ita" = italienisch	no
sessionkey	SeesionKey from "do_message.asp	string	this field or DATEFROM and DATETO are mandatory	yes
DATEFROM	begin of requested timerange	string	Format: YYYYMMDD	yes
DATETO	end of requested timerange	string	Format: YYYYMMDD Maximum time range is 7 days	yes
timefrom	more precise of DATEFROM	string	Format: HHMMSS	no
timeto	more precise if DATETO	string	Format: HHMMSS	no
datatype	"insertdate" returns all states which are processed/inserted at data center in the requested timerange	string		no

Return

A **string** will be returned. In case of error "**ERROR:Description**" is given.

Query by Sessionkey

Metainformations

Delimiter	Comma (,)
Text Delimiter	not available
Line End	0x0D 0x0A (CarriageReturn LineFeed)
Header	Line 1

Columns

Column	Description	
DATE	Date of state action	Format: DD.MM.YYYY HH:MM:SS
STATE	Description of state action	
SOURCE	source of state action	Person/Vehcile

Example

```
DATE,STATE,SOURCE
04.08.2010 09:48:41,Nachricht gelöscht,PND / Fahrzeugname
04.08.2010 09:43:24,Nachricht gelesen,PND / Fahrzeugname
04.08.2010 09:42:24,Zugestellt,PND / Fahrzeugname
04.08.2010 09:41:54,Zustellungsversuch,PORTAL / RTI
```

Return via time range

Metainformations

Delimiter	Comma (,)
Text Delimiter	Double Quote (")
Line End	0x0D 0x0A (CarriageReturn LineFeed)
Header	Line 1

Columns

Spalte	Beschreibung	
DATE	Date of state action	Format: DD.MM.YYYY HH:MM:SS
STATE	Description of state action	
SOURCE	source of state action (Person)	
SRCNAME	source of state action (System)	
KEY	Sessionkey of message	
REQUESTDATE	Systemtime of request	Format: DD.MM.YYYY HH:MM:SS
INSERTDATE	Systemtime of insert	Format: DD.MM.YYYY HH:MM:SS

Example

```
"DATE", "STATE", "SOURCE", "SRCNAME", "KEY", "REQUESTDATE", "INSERTDATE"
"04.08.2010 09:48:41", "Nachricht gelöscht", "PND", "Fahrzeugname", "ABABABABABABABABABABABABABABABAB", "04.08.2010
09:50:00", "04.08.2010 09:49:23"
"04.08.2010 09:43:24", "Nachricht gelesen", "PND", "Fahrzeugname", "ABABABABABABABABABABABABABABABAB", "04.08.2010 09:
50:00", "04.08.2010 09:44:10"
"04.08.2010 09:42:24", "Zugestellt", "PND", "Fahrzeugname", "ABABABABABABABABABABABABABABABAB", "04.08.2010 09:50:00", "
04.08.2010 09:43:11"
"04.08.2010 09:41:54", "Zustellungsversuch", "PORTAL", "RTI", "ABABABABABABABABABABABABABABABAB", "04.08.2010 09:50:
00", "04.08.2010 09:42:11"
```

Example Calls

Query by SessionKey

```
https://map.yellowfox.de/rti/get_messagestate.asp?
company=COMPANY_RTIKEY&vehicle=VEHICLE_RTIKEY&language=deu&sessionkey=SESSION_KEY
```

Query by time range based on insert date

`https://map.yellowfox.de/rti/get_messagestate.asp?
company=COMPANY_RTIKEY&vehicle=VEHICLE_RTIKEY&language=deu&DATEFROM=TT.MM.JJJJ&DATETO=TT.MM.
JJJJ&timefrom=HHMMSS&timeto=HHMMSS&datetype=insertdate`